




HARD STONE

Alberto S. **TEX**alive Industrial
 Texalve Technologies, S.L. (Spain)
 P. I. Salinetas, Calle Penya del Sol, 3 03610 Petrer (Alicante) Tfn. 966 440 579
 texalive@texalve.es www.texalve.es
 www.texalve.es

Texalve Technologies, S.L.


Thickness	Weight	Width	Substrate	Finishing Process
1.8mm ± 0.1 <i>1.2</i>	800g ± 70	140CM (Standard)	Nylon Microfiber	Dry coating (Waterborne PU)



- Design for comfort dry
- Low weight
- Durability
- Strong



ED01




ED02



ED03




ED04




ED05




ED06




ED07




ED08



ED09



ED10



Waterborne Polymer	Light Weight	Seamless	Leather Replacement	Low Absorption	Fast Drying	Breathable	Abrasion Resistance	Recyclable



Texalive Technologies, S.L.

SAFETY 16/18/21

Alb... **TEXalive** Industrial
 Texalive Technologies, S.L. - Spain)
 P. I. Salinetas, Calle Peña del Sol, 3 440 579
 03610 Petrer (Alicante)
 Tfno. 966 440 579
 texalive@texalive.es www.texalive.es 109 068
 texalive@texalive.es
 www.texalive.es

EN-ISO 20345



SSW01



SSW02



SSW03



SSW04



SSW05



SSW06



SSW07



SSW08



SSB01



SSB02



SSB03



SSB04



SSB05



SSB06



SSB07



SSB08